



## Gas LP Montacarga Forklift 3 Ton Lpg Gasoline Powered Forklift 1070mm Fork Length

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FG30
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



### Product Specification

- Model Number: FG25 FG30 FG35
- Rated Loading Capacity: 2.5 TON 3 Ton 3.5 TON
- Core Components: Pump, Gearbox, Engine
- Weight (KG): 4300 Kg
- Fork Length: 1070mm
- Fork Width: 125mm
- Overall Dimensions: 1070\*125\*45mm
- Rated Capacity: 3000kg
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: **lpg gasoline powered forklift ,**



for more products please visit us on [rdforklift.com](http://rdforklift.com)

## PRODUCT DETAILS

GOODSENSE 3 ton LPG forklift trucks bring power, dependability, productive forces and a low cost of property to operations across industry.

With a conventional automotive layout, GOODSSENSE 3 ton LPG forklift trucks are easy to use, simple to service and come with a range of standard characteristics and added choices.

With lift heights up to 6000mm, lift capacities from 1,500kg up to 3,000kg, empty load travel speeds up to 20km/h and excellent mobility, control and visibility, GOODSSENSE 3 ton LPG forklift trucks adapt to the needs of various businesses such as constructors, retailers, manufacturers, logistics, warehousing and much more.

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |

| Model                                      |                                      |     | FF<br>GG<br>22<br>05                                           | FG30           | FG35           |
|--------------------------------------------|--------------------------------------|-----|----------------------------------------------------------------|----------------|----------------|
| Power Type                                 |                                      |     | LL<br>PP<br>GG                                                 | LPG & Gasoline | LPG & Gasoline |
| Rated Capacity                             |                                      | kg  | 22<br>05<br>00<br>00                                           | 3000           | 3500           |
| Load Centre                                |                                      | mm  | 55<br>00<br>00                                                 | 500            | 500            |
| Lift Height                                |                                      | mm  | 33<br>00<br>00<br>00                                           | 3000           | 3000           |
| Fork Size                                  | L×W×T                                | mm  | 11<br>00<br>77<br>00<br>××<br>11<br>22<br>00<br>××<br>44<br>00 | 1070×125×45    | 1070×125×50    |
| Mast Tilt Angle                            | F/R                                  | Deg | 66<br>°/°/<br>11<br>22<br>°°                                   | 6°/12°         | 6°/12°         |
| Front Overhang (Wheel center to fork face) |                                      | mm  | 44<br>44<br>55                                                 | 480            | 485            |
| Ground Clearance(Bottom of mast)           |                                      | mm  | 88<br>00                                                       | 140            | 140            |
| Overall Dimension                          | Length to face of fork(Without fork) | mm  | 22<br>33<br>55<br>55                                           | 2730           | 2775           |
|                                            | Overall Width                        | mm  | 11<br>11<br>11<br>00                                           | 1225           | 1225           |
|                                            | Mast Lowered Height                  | mm  | 22<br>00<br>77<br>00                                           | 2115           | 2115           |

|                                      |                                     |      |                             |              |              |
|--------------------------------------|-------------------------------------|------|-----------------------------|--------------|--------------|
|                                      | Mast Extended Height(With backrest) | mm   | 44007700                    | 4150         | 4150         |
|                                      | Overhead Guard Height               | mm   | 22008800                    | 2090         | 2090         |
| Turning Radius (outside)             |                                     | mm   | 22111100                    | 2440         | 2480         |
| Speed                                | Travel (Full load)                  | km/h | 1177                        | 20           | 20           |
|                                      | Lifting (Full load)                 | mm/s | 553300                      | 510          | 440          |
| Max.Gradeability (No load/Full load) |                                     | %    | 2200                        | 20           | 20           |
| Tire                                 | Front                               | mm   | 2211**77**1155              | 28×9-15-12PR | 28×9-15-12PR |
|                                      | Rear                                | mm   | 1166(1/1/4)**66**111(1/1/4) | 6.50-10-10PR | 6.50-10-10PR |
| Wheelbase                            |                                     | mm   | 11440000                    | 1700         | 1700         |
| Service weight                       |                                     | kg   | 33464555                    | 4300         | 4500         |
| Battery                              | Voltage/Capacity                    | V/Ah | 112/2/8800                  | 12/80        | 12/80        |
| Engine                               | Model                               |      | K25EPA                      | K25          |              |
|                                      | Manufacture                         |      | GCT (NISSAN)                | GCT (NISSAN) |              |
|                                      | Rated output/r.p.m.                 | kw   | 42/2700                     | 35.6/2100    |              |
|                                      | Rated torque/r.p.m.                 | N·m  | 185/1350                    | 176.5/1600   |              |
|                                      | No.of Cylinder                      |      | 4                           | 4            |              |
|                                      | Bore×Stroke                         | mm   | 89×100                      | 89×100       |              |
|                                      | Displacement                        | cc   | 2488                        | 2488         |              |
|                                      | Fuel Tank Capacity                  | L    | 55                          | 60           | 60           |

|              |                     |  |           |           |
|--------------|---------------------|--|-----------|-----------|
| Transmission | Type                |  | Hydraulic | Hydraulic |
|              | Standard<br>FWD/RVS |  | 1/1       | 1/1       |



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjg\_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China