



# Full Battery Lifter Forklift 3.5 Ton 3 Ton Warehouse Electric Counterbalance Forklift With Imported Engine

### **Basic Information**

Place of Origin: China
Brand Name: Goodsense
Model Number: FB30
Minimum Order Quantity: Negotiable
Price: Negotiable
Packaging Details: Bare packaging
Delivery Time: 30-40work days

• Payment Terms: T/T



## **Product Specification**

Model Number: FB30Rated Loading Capacity: 3 TON

• Core Components: Pressure Vessel, Motor, Bearing, Gear,

Pump, Gearbox

Weight (KG): 3000 Kg
 Fork Length: 1070mm
 Fork Width: 125mm

• Overall Dimensions: 3685mm\*1230mm\*2115mm

Rated Capacity: 3000kg
Place Of Origin: China
Brand Name: Goodsense
Name: Forklift
Condition: New

Energy Supply: Reference IntroductionAdvantage: Small Vibration And Noise



| Product Description |  |
|---------------------|--|
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |
|                     |  |

## advantages

## **Product Parameter**

| Model                                      | FB30              | FB35              |
|--|-------------------|-------------------|
| Rated Capacity                             | 3000kg            | 3500kg            |
| Load Centre                                | 500mm             | 500mm             |
| Lift Height                                | 3000mm            | 3000mm            |
| Fork Size (L×W×T)                          | 1070mm×125mm×45mm | 1070mm×125mm×50mm |
| Length to fork face of fork (Without fork) | 2610mm            | 2615mm            |
| Overall Width                              | 1230mm            | 1230mm            |
| Mast Lowered Height                        | 2110mm            | 2115mm            |
| Mast Extended Height (With backrest)       | 4180mm            | 4180mm            |
| Overhead Guard Height                      | 2250mm            | 2250mm            |
| Turning Radius (outside)                   | 2350mm            | 2350mm            |
| Front Overhang(Wheel center to fork face)  | 480mm             | 485mm             |
| Tread (Front/Rear)                         | 1000mm/980mm      | 1000mm/980mm      |

| Ground Clearance(Bottom of mast) | 140mm        | 140mm        |
|----------------------------------|--------------|--------------|
| Wheelbase                        | 1700mm       | 1700mm       |
| Fork Spread (Min./Max)           | 250mm/1100mm | 250mm/1100mm |
| Travel Speed                     | 14km/h       | 14km/h       |
| Lifting Speed(Full load)         | 300mm/s      | 280mm/s      |
| Max.Gradeability                 | 15%          | 15%          |
| Service Weight                   | 5100kg       | 5350kg       |

With technological innovation, our product configuration and parameters will continue to change without notice;

if there is any doubt, the specific confirmation of our international trade sales shall prevail.

#### **Product Feature**

- 1. This electric forklift has an Original imported world famous brand controller. After professional adjustment, walking and upgrade control is precision and efficiency, excellent performance. The forklift with regenerative braking, ramp braking, fault self-diagnosis and other functions.
- 2. Using dynamic load sensing priority steering system, steering response more quickly, driving more smoothly.
- 3. Advanced H-type remote drive unit, compact structure, lower gravity center, more reasonable layout, more stable driving.
- 4. Fully open hood, it can quickly remove from both side. Hinge design frame side door. The using of advanced design concept of battery replacement program, gives fast and convenient maintenance.

