

Full Battery Lifter Forklift 3.5 Ton 3 Ton Warehouse Electric Counterbalance Forklift

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FB30
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



Product Specification

- Model Number: FB30
- Rated Loading Capacity: 3 TON
- Core Components: Pressure Vessel, Motor, Bearing, Gear, Pump, Gearbox
- Weight (KG): 3000 Kg
- Fork Length: 1070mm
- Fork Width: 125mm
- Overall Dimensions: 3685mm*1230mm*2115mm
- Rated Capacity: 3000kg
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise



More Images



for more products please visit us on rdforklift.com

Product Description

Our Product Introduction

for more products please visit us on rdforklift.com

advantages

Product Parameter

Model	FB30	FB35
Rated Capacity	3000kg	3500kg
Load Centre	500mm	500mm
Lift Height	3000mm	3000mm
Fork Size (L×W×T)	1070mm×125mm×45mm	1070mm×125mm×50mm
Length to fork face of fork (Without fork)	2610mm	2615mm
Overall Width	1230mm	1230mm
Mast Lowered Height	2110mm	2115mm
Mast Extended Height (With backrest)	4180mm	4180mm
Overhead Guard Height	2250mm	2250mm
Turning Radius (outside)	2350mm	2350mm
Front Overhang(Wheel center to fork face)	480mm	485mm
Tread (Front/Rear)	1000mm/980mm	1000mm/980mm

Ground Clearance(Bottom of mast)	140mm	140mm
Wheelbase	1700mm	1700mm
Fork Spread (Min./Max)	250mm/1100mm	250mm/1100mm
Travel Speed	14km/h	14km/h
Lifting Speed(Full load)	300mm/s	280mm/s
Max.Gradeability	15%	15%
Service Weight	5100kg	5350kg

With technological innovation, our product configuration and parameters will continue to change without notice;

if there is any doubt, the specific confirmation of our international trade sales shall prevail.

Product Feature

1. This electric forklift has an Original imported world famous brand controller. After professional adjustment, walking and upgrade control is precision and efficiency, excellent performance. The forklift with regenerative braking, ramp braking , fault self-diagnosis and other functions.
2. Using dynamic load sensing priority steering system, steering response more quickly, driving more smoothly.
3. Advanced H-type remote drive unit, compact structure, lower gravity center, more reasonable layout, more stable driving.
4. Fully open hood, it can quickly remove from both side. Hinge design frame side door. The using of advanced design concept of battery replacement program, gives fast and convenient maintenance.



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjg_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China